



# REP CL 06 LR . CANTILEVER TAIL-LIFT WITH MANUAL OPENING - 1 CYLINDER

LOAD CAPACITY  
• 600 KG


## TECHNICAL SPECIFICATIONS

Cylinders:	1 lift cylinder
Tilt cylinders:	No
Automatic tilt at ground level:	No
Platform type:	Semi level-ride
Platform opening:	Manual
Platform material:	Aluminium / Aluminium
Standard platform widths Alu:	Max 2000
Lift arm lengths:	C - H
Lift arm widths (W):	610 mm
Standard control unit:	Exterior control box with joystick, turn button
Weights incl. CE bumper	

## APPLICATIONS

The REP CL 06 LR cantilever tail-lifts with manual opening are the ideal tail-lifts for logistic companies, vehicle rental companies and tool hire companies.

REP CL 06 LR is very light and compact. Therefore, it is suitable for smaller vehicles from 3,5 to 7 tons and pick-up.



Mod.	Load capacity (centre to centre at 600 mm)	Standard platform dimensions Deep x Width	Weight *	A		E	B	T
				min.	max.	max.	min.	
REP CL 06 LR	600 Kg	1100 x 2000 mm***	225 Kg					
		1300 x 2000 mm***	240 Kg	350 mm	470 mm	1000 mm	907 mm	150 mm
		1500 x 2000 mm***	255 Kg					



\*\*\*2000 mm (78" 3/4) width available - weight 239 Kg (526 lbs). \*\*\*2300 mm (90") width max; decreased width available on request.  
Centre of gravity of the vehicle depending on the type of platform and the size of the installations on the vehicle (see assembly instructions).

The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.